

testo 106

The core thermometer testo 106 with a thin, robust measuring tip, excellently suited for fast core temperature monitoring in gastronomy, in hotels, large kitchens, supermarkets etc.

The Compact Food Thermometer With Alarm

- Audible and optical alarm (LED lights up)
- TopSafe, waterproof and dishwasher-safe protective case (IP 67)
- Fast measurement (2 measurements per second)
- Almost invisible penetration hole due to special food probe
- BS EN 13485 compliant when used with TopSafe
- Automatic recognition of final value (Auto-Hold)



Audible and optical alarm (LED lights up)

testo 106

testo 106, core thermometer incl. probe protecting cap and battery

Part no. 0560 1063



Accessories

- 1 TopSafe (indestructible protection case)**
waterproof and dishwasher-safe protection case (IP67)
- 2 Probe protecting cap,**
protects you from injury
- 3 Practical belt-clip,**
loss-proof attachment to belt clip
- 4 Frozen food drill,**
loss-proof attachment to belt clip



Almost invisible penetration hole due to special food probe

Set testo 106

Set testo 106, core thermometer incl. TopSafe (waterproof protective case, IP 67), belt clip, probe protecting cover and battery

Part no. 0563 1063



Waterproof and protected from impact with protective case TopSafe

Accessories Ordering data

Accessories Ordering data	Part no.
Frozen food drill, loss-proof attachment to belt clip	0554 0826
TopSafe (indestructible protection case), waterproof and dishwasher-safe protection case (IP67)	0516 8265
Holding clip with probe protection cap	0554 0825
ISO calibration certificate/temperature, for air/immersion probes, calibration point +60°C	300520 0048
ISO calibration certificate/temperature, for air/immersion probes, calibration point -18°C	300520 0056
ISO calibration certificate/temperature, for air/immersion probes, calibration point 0°C	300520 0074
ISO calibration certificate/temperature, for air/immersion probes, calibration points -18°C; 0°C	300520 0044
ISO calibration certificate/temperature, for air/immersion probes, calibration points -8°C; 0°C; +40°C	300520 0040

Technical data

Meas. range	-50 to +275 °C		
Accuracy	±1 °C (+100 to +275 °C)	±1 °C (-50 to -30.1 °C)	
	±1 digit		
Resolution	0.1 °C	Battery life	350 h
Oper. temp.	-20 to +50 °C	Dimensions	215 x 34 x 19 mm
Storage temp.	-40 to +70 °C	Weight	80 g



Fast and robust measuring tip